Rev 06



Model: **B-383DK**

Typology: ROUTINE MICROSCOPE

Description:

Educational and laboratory microscope for routine applications.

Dye-cast frame, with high stability and ergonomy, for transmitted light observation.

Illumination	Light source: X-LED³; light intensity control using a knob on left side of the frame. LED power: 3.6W, comparable to a 50W halogen bulb. Color temperature: 6300K LED average lifetime: 50000h. Darkfield illuminator based on high efficiency LED. Power supply: Input 110/240Vac, 50/60Hz; Output 6Vdc 1A Max. required power: 6W
Observation modes	Brightfield, darkfield.
Focusing	Coaxial coarse and fine focusing mechanism (graduated, 0.002mm) with upper stop, to prevent the contact between objective and specimen. Adjustable tension of coarse focusing knob.
Stage	Double layer mechanical sliding stage, size 160x140mm, moving range 78x54mm. Vernier scale on the two axes, accuracy 0,1 mm.
Nosepiece	Quintuple revolving nosepiece, rotation on ball bearings.
Head	Trinocular observation head, inclined 30° and rotatable 360°. Diopter adjustment on left eyepiece. Interpupillary adjustment 48-75 mm. Fixed photo port, 50/50 ratio.
Eyepieces	Widefield eyepieces WF10X/20 with field number 20.
Objectives	Objectives with 160mm mechanical tube length: -) E-Plan 4X, N.A. 0.10, W.D. 15.2 mm -) E-Plan 10X, N.A. 0.25, W.D. 5.5 mm -) E-Plan 40X, N.A. 0.65, W.D. 0.45 mm -) PlanAchromatic 100X with iris, N.A. 1.25, W.D. 0.1 mm (oil immersion) All objectives are treated with an anti-fungus treatment.
Condenser	Abbe condenser, N.A. 1.25 with centering system. Darkfield condenser N.A. 1.36 with built-in X-LED.
Dimensions	HEIGHT: 480 mm WIDTH: 210 mm DEPTH: 370 mm WEIGHT: 8 kg
Accessories	Centering Telescope included. Instruction manual and dust cover included.