

LED Ring Light

RL12-18f B

100-007715



- Solid aluminium housing in modern design
- Flicker-free lighting thanks to optimized electronic
- Brightness adjustable from 0 to 100%
- Huge illuminance
- Ideal for industry and machine vision
- Homogeneous illumination in the entire working range
- Variable clamping diameter, adaptable with reducing rings
- Various light colors and color temperatures available

Technical Data	
Working distance	50 mm - 800 mm
Optimum working distance	approx. 140 mm
Light color	blue (470 nm)
Number of LED	12 × Power-LED (Flood)
LED life span	50.000 h (according to manufacturer)
Height	42 mm
Outer diameter	130 mm
Inner diameter	66 mm
Clamping diameter	max. 66 mm
Inner thread	M67 × 0,75
Material	anodized aluminium
Color	titanium and black
Weight Ring Light	approx. 750 g

Technical Data	
Input power supply	100 - 240 V AC, 50 - 60 Hz
Output power supply	24 V DC, 1 A
Power consumption	approx. 15 W
Dimensions control unit (l×w×h)	78 mm × 38 mm × 21 mm

Accessories

- Diffusor and protection glasses
- Polarisation filter sets
- Various reducing rings
- Extensions for connector cables

**MADE
IN
GERMANY**

